

THE GRIPPER GASKET™ SUBMITTAL



Part

- A** = Stainless Steel
- B** = SBR
- C** = nominal pipe size
- D** = USA
- E** = Gripper Gasket™

Gripper Gasket™ Suggested Specification

Gripper Gasket™ 3" - 24":

Joint restraint for ductile iron water systems including pipe, valves and fittings shall be accomplished using integral boltless restraining gaskets. Pressure rating 350 psi. These gaskets shall be designed, manufactured and tested in accordance with AWWA C111/A21.11. Certified to NSF/ANSI 61. Boltless restraining gaskets shall be Gripper Gasket™ or equivalent.

MADE IN THE U.S.A. (ARRA Statement) The ARRA 2009 "Buy American" Provisions

American Recovery Reinvestment Act (ARRA) Section 1605 "Buy American" Requirements

Gripper Gasket LLC products comply with the American Recovery Reinvestment Act, Section 1605. Our products have always been manufactured in the United States of America. We take great pride in manufacturing only top quality "Made in the U.S.A." gaskets.

Gripper Gasket LLC cannot certify that accessories used with our products, such as pipe, valves, fittings, gauges, instrumentation or like components are made in the U.S.A. We pledge to encourage the use of products made in the U.S.A.